



STRATA CONTROL SERVICES, INC.  
P. O. Box 272 \* Crowley, La 70527

1-888-656-0001 Toll Free  
1-337-785-0000 Direct  
1-337-785-0004 Fax:  
E-Mail: [stratinc@bellsouth.net](mailto:stratinc@bellsouth.net)  
WWW: STRATACONTROL.COM

---

---

## STRATA-LUBE™

**STRATA LUBE™** is liquid friction reducer comprised of a blend of two superior lubricating agents, composed of a synthetic lubricant coupled with a fatty acid. **STRATA-LUBE™** is used primarily in drilling applications where problems associated with torque, drag, and the inability to slide, exist. **STRATA-LUBE™** is compatible with synthetic oils that may be present, or added to the mud system.

**STRATA-LUBE™** can be used in conjunction with **STRATA-SCM®**, **STRATA-FLEX®** and/or **STRATA-VANGUARD®**, to enhance the sealing capacity of a mud system while aiding with lubricity and general filter cake quality. A coupler should be added to a mud, which contains both **STRATA-LUBE™** and **STRATA-TROL®**.

### **BENEFITS:**

- Torque & Drag reduction.
- Sliding enhancement and efficiency, while motor drilling.
- Coating of B.H.A.
- Prevention of Bit balling.
- R.O.P. enhancement.
- Effective in Water or mud.
- Non-Hydrocarbon.
- Non-aromatic (Won't damage rubber goods)
- Non-Toxic (LC50 – 1,000,000 ppm @ 3% in generic number 7 mud)
- Non-flammable
- Non-combustible.

### **APPLICATION:**

Systems treatments are recommended in a range of 1.0% to 3.0%. Batch pill formulations, for optimized lubricity, range from 3.0% to 8.0%, depending on the degree of problems encountered. Batch pill sweeps, for enhanced horizontal motor sliding, range from 3.0% to 15.0%, and may be mixed in the drilling mud or drill water, then swept through the well bore as necessary. Usually 1-2 drums per 50 bbls of fluid will provide a sweep of superior lubricity.

### **PACKAGING:**

- Available in sealed 55-gallon plastic drums
- 4 drums per pallet – banded and shrink wrapped for transport safety

***“THE MUD STOPS HERE!®”***